

## 1U 2.4GHz 40dBm Low Latency Wireless Transmission System Vehicle Mounted Video Transmitter

Our Product Introduction

for more products please visit us on [zkmanet.com](http://zkmanet.com)

### Basic Information

- Place of Origin: Guangdong, China
- Brand Name: ZKMANET
- Certification: CE, ISO9001
- Model Number: ZKManet2361UM
- Minimum Order Quantity: 1 piece
- Price: USD 4599~6299 per piece
- Packaging Details: carton
- Delivery Time: 3-7 work days
- Payment Terms: T/T, Western Union, MoneyGram
- Supply Ability: 10000 pieces per year




### Product Specification

- Working Frequency: 1.4GHz, (300MHz-3.8GHz Customizable)
- Working Bandwidth: 5/10/20/40MHz
- RF Channel: 2T2R
- Output Power: 2\*37dBm
- Throughput Rate: 82Mbps
- Encryption: AES
- Public Network: 4G/5G Full Netcom
- WIFI: 2.4GHz
- Working Temperature: -40°C~+65°C
- Coverage Distance: 20-40KM(line-of-sight)




### More Images






### Product Description

#### Product Description

Product Description

The ZKManet2361UM is a highly flexible Mesh rack-mounted product that can be used in various communication

Our Product

combinations for different scenarios. It can be installed at fixed points or used on moving vehicles, ships, etc., allowing for on-the-go usage with one-click startup without the need for configuration or parameter changes. It is mainly used to achieve multimedia interconnection between vehicles and between ships.

## Features

- \* Data rate up to 82Mbps
- \* Range up to 20~40km
- \* Supports two-way intercom
- \* Supports MESH/4G/5G transmission
- \* Supports 2.4GHz WIFI
- \* Supports transparent IP data transmission

## Specifications

<b>Model</b>	ZKManet2361UM	<b>Brand</b>	ZKMANET
<b>RF Parameters</b>	<b>Frequency</b>	1.4GHz (300MHz-3.8GHz customizable)	
	<b>Bandwidth</b>	5/10/20/40MHz	
	<b>RF Channel</b>	2T2R	
	<b>Output Power</b>	2*37dBm	
<b>Network Parameters</b>	<b>Network Size</b>	64 nodes	
	<b>Data Rate</b>	82Mbps	
	<b>Encryption</b>	AES	
	<b>Public Network</b>	4G/5G	
	<b>WIFI</b>	2.4GHz	
<b>Physical/Environment</b>	<b>Range</b>	20-40km (LOS)	
	<b>Dimensions</b>	483*250.5*45mm (1U)	
	<b>Weight</b>	4.3kg	
	<b>Working Temp</b>	-40°C~+65°C	
<b>Electronic Parameters</b>	<b>Power Supply</b>	DC24V	
	<b>Power Consumption</b>	<60W	
<b>Other</b>	<b>Positioning</b>	Support	
	<b>Intercom</b>	Support	
	<b>LAN port</b>	Support	

## Dimensions



## Panel Description

1u Rack Mount 2T2R Voice Intercom 4G/5g/Mesh Video Transmission Radio		1. Power push button 2. MESH signal indicator 3. Micro SIM card slot 4. Mic input - LEMO 7-pin 5. LAN input
1. MESH antenna interface 1 - N F 2. MESH antenna interface 2 - N F 3. GPS antenna interface 4. 4G antenna interface 5 HDMI input interface 6 WIFI antenna interface 7 LAN input 8 DC input - 12V 9 AC input - 220V	1u Rack Mount 2T2R Voice Intercom 4G/5g/Mesh Video Trans	

## Application

1u Rack Mount 2T2R Voice Intercom 4G/5g/Mesh Video Transmission Radio

## Company Profile

1u Rack Mount 2T2R Voice Intercom 4G/5g/Mesh Video Transmission Radio1u Rack Mount 2T2R Voice Intercom 4G/5g/Mesh Video Transmission Radio1u Rack Mount 2T2R Voice Intercom 4G/5g/Mesh Video Transmission Radio

1u Rack Mount 2T2R Voice Intercom 4G/5g/Mesh Video Transmission Radio

1u Rack Mount 2T2R Voice Intercom 4G/5g/Mesh Video Transmission Radio1u Rack Mount 2T2R Voice Intercom 4G/5g/Mesh Video Trans

## FAQ

1u Rack Mount 2T2R Voice Intercom 4G/5g/Mesh Video Transmission Radio1u Rack Mount 2T2R Voice Intercom 4G/5g/Mesh Video Trans



+86 13266718951



Info@chinamanet.com



zkmanet.com

203-B161, Block B, Garden City Digital Building, No.1079 Nanhai Avenue, Yanshan Community, Merchants Street, Nanshan District, Shenzhen, China