

## Mini 1W Handheld COFDM HDMI/CVBS Video Transmitter with H.264 Encoding and 1~2km Transmission Distance

Our Product Introduction

for more products please visit us on [zkmanet.com](http://zkmanet.com)

### Basic Information

- Place of Origin: Shenzhen, China
- Brand Name: ZKMANET
- Certification: CE, ISO9001
- Model Number: ZKManet1131T
- Minimum Order Quantity: 1
- Price: USD 1999 Per Piece
- Packaging Details: Brown Carton
- Delivery Time: 4 working weeks
- Payment Terms: T/T, Western Union
- Supply Ability: 10000 pieces per year




### Product Specification

- Frequency: 300MHz-2.7GHz Customizable(700MHz Default)
- Modulation Type: QPSK(4QAM), 16QAM, 64QAM
- Bandwidth: 2-8MHz
- Encryption: AES256
- Output Power: 1W
- Transmission Distance: 1~2KM
- Video Compression: H.264
- Video Input: HDMI/CVBS




### More Images






### Product Description

**Mini 1W Handheld COFDM HDMI/CVBS Video Transmitter with H.264 Encoding and 1~2km Transmission Distance**

Product Description

Our Product

The ZKManet1131T is a mini COFDM video transmitter specifically designed for covert video transmission applications. Its small size makes it ideally for covert video transmission or applications require battery power such as body-worn use. It can be placed in briefcase, backpack or small bags, the live video can be transmitted to the rear end as secret evidence. It can be used in public security, police law enforcement, video surveillances under complex environments.

#### Features

- \* 300-2700MHz frequency customizable
- \* Supports HDMI/CVBS dual video inputs
- \* Low latency
- \* Transmission range up to 1-2km NLOS
- \* AES256 encryption
- \* Compact size and light weight
- \* Rugged aluminum alloy housing

#### Specifications

Model	ZKManet1131T	Brand	ZKMANET
RF Parameters	Frequency	300MHz-2.7GHz (Default 700MHz)	
	Modulation Type	QPSK(4QAM), 16QAM, 64QAM	
	Bandwidth	2-8MHz	
	Encryption	AES	
	Output Power	30dBm	
	RF Interface	SMA-F	
	Range	1~2KM	
Video Parameters	Video Input Interface	HD: HDMI	
		SD: 3.5mm/2.5mm interface	
	Video Input	HD: 1080P/1080i/720P/720i	
		SD: P/N	
Physical/Environment	Video Compression	H.264	
	Dimensions	120*65*30mm	
	Weight	354g (w/o battery), 238g (w/ battery)	
	Working Temp	-10°C~+65°C	
Electrical Parameters	Battery Capacity	1250mAh	
	Power Supply	DC12V	
	Power Consumption	<12W	

#### Panel Description

1. Antenna Interface - SMA F
2. Power Switch - Switch left and right
3. Power Indicator - Green light
4. HDMI Input - Mini HDMI
5. 2.5mm Video Input - 3 pins (5V, Video, GND)
6. 3.5mm Video Input - 4 pins (12V, Video, Audio, GND)
7. Micro USB Interface - Be used to connect with programmer
8. 12V DC Input - Power input

[Rugged 30dBm AES 300~2700MHz Customizable Mini Cofdm](#)

#### Application

[Rugged 30dBm AES 300~2700MHz Customizable Mini Cofdm Video Transmitter](#) [Rugged 30dBm AES 300~2700MHz Customizable Mini Cofdm](#)

#### Company Profile

Zhongke Lianxun (Shenzhen) Technology Co., Ltd is a high-tech R&D enterprise. Our products mainly use Mesh and LTE as core technologies and auxiliary decision-making software to form underground building emergency communication systems, and police investigation communication systems, and police noncombat training communication systems, urban emergency communication systems, emergency communication vehicle communication systems, etc., suitable for law enforcement forces and government departments such as public security, armed police, , forest fire prevention, civil air defense, and maritime. Especially the intelligent communication products of special robots have solved the long-distance communication and control problems of robots in complex environments.

Adhering to the principles of "unity and dedication, technological innovation, and service innovation," we serve users both domestically and internationally. We uphold the tenet of "quality first, reputation first" to provide high-quality, efficient, and customized services to our clients worldwide. The company is committed to promoting an innovative spirit of "exploration and progress."

[Rugged 30dBm AES 300~2700MHz Customizable Mini Cofdm Video Transmitter](#) [Rugged 30dBm AES 300~2700MHz Customizable Mini Cofdm Video Transmitter](#) [Rugged 30dBm AES 300~2700MHz Customizable Mini Cofdm Video Transmitter](#)

**Our Patents**

[Rugged 30dBm AES 300~2700MHz Customizable Mini Cofdm Video Transmitter](#)

**Test Equipments**

[Rugged 30dBm AES 300~2700MHz Customizable Mini Cofdm Video Transmitter](#) [Rugged 30dBm AES 300~2700MHz Customizable Mini Cofdm Video Transmitter](#)

**Our Advantages**

[Rugged 30dBm AES 300~2700MHz Customizable Mini Cofdm Video Transmitter](#) [Rugged 30dBm AES 300~2700MHz Customizable Mini Cofdm Video Transmitter](#)

**ZKMANET Zhongke Lianxun (Shenzhen) Technology Co., Ltd**

+86 13266718951    [info@chinamanet.com](mailto:info@chinamanet.com)    [zkmanet.com](http://zkmanet.com)

203-B161, Block B, Garden City Digital Building, No.1079 Nanhai Avenue, Yanshan Community, Merchants Street, Nanshan District, Shenzhen, China