Portable 43dBm Long Range 20-40km AES256 IP Mesh Video Sender And Receiver

Basic Information

- Place of Origin: Shenzhen, China • Brand Name: ZKMANET Certification: CE, ISO9001 Model Number: ZKManet2571UM • Minimum Order Quantity: 1 • Price: USD 1999 Per Piece Brown Carton Packaging Details: • Delivery Time: 5~8 working days • Payment Terms: T/T, Western Union
- Supply Ability:
- r: 10000 pieces per year

ZIMANET



Product Specification

- Frequency:Bandwidth:RF Channel:
- Output Power:
 - -
- Range:
- Network Capacity:
- Data Rate:
- Encryption:
- Highlight:



1.4GHz (Customizable)

ZIMANET



More Images



Product Description

Portable 43dBm Long Range 20~40km AES256 IP Mesh Video Data Sender and Receiver **Product Description**

Product Description

Our P

for more products please visit us on zkmanet.com

The ZKManet2571UM is a 43dBm MESH outdoor base station that, when paired with directional, omnidirectional, sector, and other types of antennas, can achieve wireless coverage networking for point-to-multipoint, point-to-point, and MESH self-organizing networks. It adopts advanced industrial design concepts such as surge/static protection, salt spray corrosion resistance, etc., to meet the demands of various complex electromagnetic environments and harsh weather conditions for complexies arguing the algorithm. continuous operation around the clock.

Features

- * High Power of 43dBm
 * Data rate up to 82Mbps
 * Full transparent IP data transmission
 * Rugged IP67
- * Range up to 20~40km

Specifications

			I	
Model	ZKManet2571UM	Brand	ZKMANET	
RF Parameters	Frequency	1.4GHz (Customizable)		
	Bandwidth	5/10/20/40MHz		
	RF Channel	2T2R		
	Output Power	43dBm		
	Range	20-40km		
Network Parameters	Network Size	64 Nodes		
	Data Rate	82Mbps		
	Encryption	AES		
Physical/Environ ment	Dimensions	304*184*77mm		
	Weight	4.55kg		
	Working Temp	-20ºC~+65ºC		
	IP Rating	IP67		
Electronic	Power Supply	AC220V		
Parameters	Power Consumption	<80W		

Panel Description

	2. GPS Ar 3. MESH /	Antenna Interface 1 Itenna Interface Antenna Interface 2 Signal Indicator		
	Indicator St	•	Signal Strength	
	Red flickers		No device connected	
	Red still	Red still		
	Orange still	Orange still		
43dBm Long Range IP Mesh Video Data Sender and Receiver	Green still		Strong signal	
	SNR	Indicator Color	Topology Color	Topology Va
	0	Red flicker	Red	0
	<-90	Red still	Red	<-90
	-75 to -90	Orange still	Orange	-75 to -90
	>-75	Green still	Green	>-75
3dBm Long Range IP Mesh Video Data Sender and Receiver				
3dBm Long Range IP Mesh Video Data Sender and Receiver Company Profile				
	rground building at training comm cation systems, o orest fire preven	emergency communication systems, etc., suitable for law tion, civil air defens	unication systems, urban emergency enforcement forces e, and maritime.	

43dBm Long Range IP Mesh Video Data Sender and Receiver 43dBm Long Range IP Mesh Video Data Sender and Receiver 43dBm Long Range IP Mesh Video Data Sender and Receiver

FAQ

43dBm Long Range IP Mesh Video Data Sender and Receiver

ZIMPLET Zhongke Lianxun (Shenzhen) Technology Co., Ltd



203-B161, Block B, Garden City Digital Building, No.1079 Nanhai Avenue, Yanshan Community, Merchants Street, Nanshan District, Shenzhen, China