## 4W MIMO 2x2 82Mbps HDMI AES256 Encryption Portable Mobile Mesh **Command Station Transceiver**

### **Basic Information**

- Place of Origin:
- Brand Name:
- Certification:
- Model Number:
- Minimum Order Quantity: 1 • Price:
- Packaging D
- Delivery Time
- Payment Ter
- Supply Ability

|         | USD 5899~6999         |
|---------|-----------------------|
| etails: | Brown Carton          |
| e:      | 5~8 working days      |
| rms:    | T/T, Western Union    |
| y:      | 10000 pieces per year |
|         |                       |

Shenzhen, China

ZKMANET

CE, ISO9001

ZKManet2951

# ZIMANET



## **Product Specification**

- OS: • CPU:
- Display:
- Memory:
- Frequency:
- Bandwidth:
- Output Power:
- IP Rating:
- Power:
- Data Rate:

| WIN10 64-bit                         |
|--------------------------------------|
| Intel I7                             |
| 15.6-inch HD Screen                  |
| 8G                                   |
| 1.4G Hz (300MHz-3.8GHz Customizable) |
| 5M/10M/20MHz/40MHz                   |
| 36dBm (4W MIMO 2x2)                  |
| IP65                                 |
| 4W                                   |
| 82Mbps                               |

# ZIMANET



### More Images



### **Product Description**

4W MIMO 2x2 82Mbps HDMI AES256 Encryption Portable Mobile Mesh Command Station Transceiver

#### Product Description

Our Pr

for more products please visit us on zkmanet.com

for more products please visit us on zkmanet.com

manage and set up various Mesh nodes within the network through link management, allowing users to view the signal strength of each link, video and data information of each node, display front-end video in real-time, and conduct voice intercom. The Mesh command box can serve as a front command post and can also transmit data back to the main command center through 4G/5G private networks or public networks to coordinate operations.

#### Features

- \* Integrated IPC for easy operation
- \* Infrastructure-less, self configuring and self healing
- \* Supports 1400-1480MHz (350MHz-4GHz customizable)
- \* Data rate up to 82Mbps
- \* Range up to 1-10km NLOS
- \* Supports up to 9 hops and no less than 64 nodes
- \* Full transparent IP data transmission
- \* Supports two-way intercom
- \* HDMI output as optional
- \* Supports 2.4G/5.8G WIFI and 4G connection
- \* Supports AES256 encryption
- \* Battery endurance up to 4-5 hours
- \* Rugged IP65 housing
- \* Low system latency

#### Detailed Photos

Rugged IP65 Portable Mobile Mesh Command Station Transceiver

- 1. MESH Antenna Interface
- 2. Antenna Interface (Reserved)
- 3. Data Interface (Reserved)
- 4. LAN Port (RJ45)
- 5. Power Input Port
- 6. Screen
- 7. Battery Display
- 8. USB Ports
- 9. Power Switch
- 10. Keyboard
- 11. WIFI Antenna Interface
- 12. 4G Antenna Interface
- 13. SIM Card Slot
- 14. Mic Interface
- 15. Signal Indicator
- 16. Display Switching Panel

Product Parameters

Rugged IP65 Portable Mobile Mesh Command Station Transce

| Host Characteristic        |  |                 |  |  |
|----------------------------|--|-----------------|--|--|
| OS                         | WIN10 64-bit                                       |                 |  |  |
| CPU                        | Intel I7   |                 |  |  |
| Display                    | 15.6-inch HD high-gloss screen                     |                 |  |  |
| Memory                     | 8G   |                 |  |  |
| Storage Method             | 250G Solid State Drive                             |                 |  |  |
| Mode of Operation          | Embedded Mouse and Keyboard                        |                 |  |  |
| Transmission Characteristi | cs   |                 |  |  |
| Frequency                  | 1.4G Hz (300MHz-3.8GHz customizable)               |                 |  |  |
| Bandwidth                  | 5M/10M/20MHz/40MHz                                 |                 |  |  |
| Output Power               | 36dBm (4W MIMO 2x2)                                |                 |  |  |
| Modulation                 | DSSS/CCK BPSK/QPSK OFDM<br>BPSK/QPSK/16-QAM/64-QAM |                 |  |  |
| FEC Code                   | 1/2,2/3,3/4,5/6                                    |                 |  |  |
| Digital Sensitivity        | 96dBm@5MHz BPSK                                    |                 |  |  |
| Data Rate                  | Up to 82Mbps                                       |                 |  |  |
| Network Capabilities       | 9 hops and no less than 64 nodes                   |                 |  |  |
| Data Characteristics       |  |                 |  |  |
| RF Interface               | N*2,SMA*2  |                 |  |  |
| LAN Interface              | RJ45 Waterproof Interface                          |                 |  |  |
| Intercom Interface         | 7-pin Connector                                    | 7-pin Connector |  |  |
| Video Output               | HDMI   |                 |  |  |
| Power Input                | 3-pin Aviation Connector                           |                 |  |  |
| 4G Function                | Full Network Access                                |                 |  |  |
| Signal Indicator           | 1x Dual Color Signal Indicator                     |                 |  |  |
| Power Switch               | Self-resetting Switch with Light                   |                 |  |  |
| Encryption                 | AES256   |                 |  |  |
| Electrical Characteristics |  |                 |  |  |
| Voltage & Current          | DC12 V, ≤ 3A                                       |                 |  |  |
| Power Consumption          | Average 36W  |                 |  |  |
| Battery Capacity           | 21Ah   |                 |  |  |
| Physical Characteristics   |  |                 |  |  |
| Operating Temperature      | -20~+55°C  |                 |  |  |
| Storage Temperature        | -40ºC~ +65ºC                                       |                 |  |  |
| Dimensions                 | 577*353*211mm                                      | 577*353*211mm   |  |  |
| Weight                     | 15kg(w/ Battery)                                   |                 |  |  |
| IP Rating                  | IP65   |                 |  |  |
| Company Profile            |  |                 |  |  |

Company Profile

Zhongke Lianxun (Shenzhen) Co., Ltd was established in 2005. The company focuses on the research and development of products for drone defense/control, wireless video transmission, and network security encryption/decryption. It leverages the technical expertise of renowned university network security institutes. The company specializes in providing data encryption and decryption solutions as well as drone defense solutions for industries such as wind power, national power, oil and gas, firefighting, public security, road and bridge construction, and emergency management agencies.

Rugged IP65 Portable Mobile Mesh Command Staffung jesh Res/Portable Mobile Mesh Command Staffung jesh Res/Portable Mobile Mesh (

| Our Patents<br>Rugged IP65 Portable Mobile Mesh Command Station Transceiver |  |                |  |  |  |
|---|--|----------------|--|--|--|
| Test Equipments   |  |                |  |  |  |
| Rugged IP65 Portable Mobile Mesh Command Station Transceiver                | Rugged IP65 Portable Mobile Mesh Command S | tation Transce |  |  |  |
| Our Advantages  |  |                |  |  |  |
| Rugged IP65 Portable Mobile Mesh Command Station Transceiver                | Rugged IP65 Portable Mobile Mesh Command S | tation Transce |  |  |  |
|   |  |                |  |  |  |
|   |  | 1              |  |  |  |
| ZIMP.NET Zhongke Lianxun (Shenzhen) Technology Co., Ltd                     |  |                |  |  |  |
|   | E zkmanet.com                              |                |  |  |  |

203-B161, Block B, Garden City Digital Building, No.1079 Nanhai Avenue, Yanshan Community, Merchants Street, Nanshan District, Shenzhen, China