

ZKMANET2421UM 5-15km Wireless IP Video Image Transmission UAV Drone Data Link

Our Product Introduction

for more products please visit us on zkmanet.com

Basic Information

- Place of Origin: Guangdong, China
- Brand Name: ZKMANET
- Certification: CE, ISO9001
- Model Number: ZKMANET2421UM
- Minimum Order Quantity: 1 piece
- Price: USD999/PC
- Packaging Details: carton
- Delivery Time: 137dBmork days
- Payment Terms: T/T, Western Union, MoneyGram, L/C, D/A, D/P
- Supply Ability: 10000 pieces per year



Product Specification

- Working Frequency: 800MHz, 1.4GHz, 2.4GHz
- Working Bandwidth: 1.4MHz/3MHz/5MHz/10MHz/20MHz
- RF Channel: 1T2R
- Transmit Power: 25dBm
- Coverage Distance: 5-15KM
- Dimension: 102*52*21.5mm
- Weight: 124g
- Working Temperature: -40°C~+65°C
- Power Supply: DC12V
- Power Consumption: <37dBm
- Application: Drone Uav Image Transmission



More Images



Product Description

ZKMANET2421UM 5-15km Wireless IP Video Image Transmission UAV Drone Data Link

Product Description

ZKManet2421UM is a compact and portable unmanned carrier device with high definition and stable image quality developed by our company. Adopting the current leading OFDM modulation technology, it can realize shooting and real-time transmission of high-quality images in non-line-of-sight (non-visual), high-speed movement, encrypting images and data during transmission, and supporting frequency hopping at 800MHz, 1.4GHz, 2.4GHz, transmission rate of 30Mbps and 5-15KM air-to-ground transmission, which is very suitable for long-time and high-dataflow wireless transmission applications.

Features

1. IP data transparent transmission;
2. Support webcam access;
3. Long transmission distance, line-of-sight 5-15km;
4. Supports transmission at 800MHz, 1.4GHz, 2.4GHz frequency hopping;
5. Small and portable design, aluminum alloy with good thermal conductivity, impact resistant;
6. Supports unicast, multicast, and broadcast propagation methods, and any node can communicate with each other using these three methods.

Compact Size

The transmitter is compact and lightweight, with a total weight of 124g, effectively reducing the drone's payload and enhancing its wind resistance in the air.

High Reliability

The system employs advanced Orthogonal Frequency Division Multiplexing (OFDM) modulation technology, which has strong anti-interference capabilities. It also uses AES encryption technology to effectively prevent interference and eavesdropping.

Strong Usability

Quick deployment without configuration is possible, and the system operates stably and reliably with simple maintenance.

Long Transmission Distance

Utilizing the drone's flight altitude and servo antenna tracking directional antenna technology, the transmission distance can be guaranteed at 15, 30, or longer kilometers, while the system also possesses strong diffraction and penetration capabilities.

Clear Image Transmission

The system uses H.264/MPEG-2/4 compression methods, allowing transmitted video to achieve 1080P quality, clearly presenting images captured by the drone to the user.

Product Parameters

Item No.	ZKMANET2421UM	BRAND	ZKMANET
RF Parameters	Working Frequency	800MHz, 1.4GHz, 2.4GHz	
	Working Bandwidth	1.4MHz/3MHz/5MHz/10MHz/20MHz	
	RF Channel	1T2R	
	Transmit Power	25dBm	
	Coverage Distance	5-15KM	
Network Parameters	Networking Methods	Point to point, point to multi-point	
	Throughout Rate	30Mbps(Max)	
	Encryption	ZUC,SNOW3G,AES 3 encryption methods available	
	Conflict Management	When two or more self-organized networks interfere with each other, automatic frequency tuning or bandwidth reduction is performed.	
Physicals/Environments	Dimension	102*52*21.5mm	
	Weight	124g	
	Working Temperature	-40°C~+65°C	
Electrical Characteristics	Power Supply	DC12V	
	Power Consumption	<37dBm	
Other	Data Interfaces	RJ45*2,TTL*1	

Detailed Photos

- 1. Power Cables - power supply input line, red is VDD, black is GND
- 2. Data UART Port (GND, Rx, Tx) - 3.3V TTL
- 3. Link Status Indicator - When the device works as an access node, if the connection with the central node is normal, the indicator will be always on. When the device works as a central node, this indicator is off.
- 4. Micro USB Port - For device software maintenance.
- 5. Indicator (Red) for Power - Always on during normal operation.

15km Coverage Distance Drone Airborne Vehicles Wireless Video Receiver

- 6. Indicator for Ethernet Port 2 - Flashes according to the data flow when works normally.
- 7. Ethernet Port 2 (RN, RP, TN, TP) - Ethernet port 1 and 2 are internally bridged
- 8. Indicator for Ethernet Port 1 - Flashes according to the data flow when works normally.
- 9. Ethernet Port 1 (RP, RN, TP, TN) - Ethernet port 1 and 2 are internally bridged.

- 1. Product Label
- 2. Air Inlet - for the cooling fan
- 3. ANT2 Port - Auxiliary antenna, works as auxiliary receiving, NO transmitting.
- 4. ANT1 Port - Main antenna, work mode is TDD transmitting/receiving.

15km Coverage Distance Drone Airborne Vehicles Wireless Video

Application



Company Profile

Zhongke Lianxun (Shenzhen) Technology Co., Ltd is a high-tech R&D enterprise. Our products mainly use Mesh and LTE as core technologies and auxiliary decision-making software to form underground building emergency communication systems, and police investigation communication systems, and police noncombat training communication systems, urban emergency communication systems, emergency communication vehicle communication systems, etc., suitable for law enforcement forces and government departments such as public security, armed police, , forest fire prevention, civil air defense, and maritime. Especially the intelligent communication products of special robots have solved the long-distance communication and control problems of robots in complex environments.



FAQ

15km Coverage Distance Drone Airborne Vehicles Wireless Video Transmission 15km Coverage Distance Drone Airborne Vehicles Wireless Video Transmission

ZKMANET Zhongke Lianxun (Shenzhen) Technology Co., Ltd



+86 13266718951



Info@chinamanet.com



zkmanet.com

203-B161, Block B, Garden City Digital Building, No.1079 Nanhai Avenue, Yanshan Community, Merchants Street, Nanshan District, Shenzhen, China