Shenzhen

ZKMANET

USD 99~999

15 working days

1000 pieces per year

MoneyGram

L/C, D/A, D/P, T/T, Western Union,

Carton

ZKMANET2152UM

CE

1

8 Channels Alluminum Alloy Remote Controller for Environment Gas **Temperature Test ZKMANET2152UM**

Basic Information

- Place of Origin:
- Brand Name:
- Certification:
- Model Number:
- Minimum Order Quantity:
- Price:
- Packaging Details:
- Delivery Time:
- Payment Terms:
- Supply Ability:

ZIMANET



Product Specification

Color:	Black
Screen:	Double
• Frequency:	Customized
Range:	1-5km
 Material: 	Alluminum Alloy
 Application: 	UGV EOD RAV
• Size:	373*241*57mm
• Type:	Button
 Display: 	8 Channels
 Highlight: 	Environment Gas Temperature Tes

- est Remote Controller
 - , Alluminum Alloy Remote Controller,
- 8 Channels Remote Controller

ZUMANET



More Images





ZKMANET2152UM Enviroment Gas Temperature Test Double Screen 8 Channels Romote Controller

Product Description

ZKMANET2152UM is a waterproof industrial-grade remote control based on an embedded operating system. It supports customer-defined communication protocols and control protocols. The communication method adopts self-organizing network communication. The point-to-point communication reaches 1.5 kilometers in complex environments and supports 10 devices are online at the same time, fully solving the problem of mutual interference between multiple devices. It also supports public network 4G/5G transmission, and supports 1-8 channels of video transmission and network monitoring. Practical needs such as data control backhaul. The backlight adopts a slightly upward tilt of the screen, an upright antenna, and a silicone-wrapped handshake part. It feels friendly to the human-machine interface and gives full play to the optimal performance of the device.

Features

Aluminum alloy shell: strong heat dissipation, the handshake part is wrapped in silicone and comes with a strap for easy operation;

High-definition high-brightness screen: The 10.1-inch high-definition high-brightness screen is visible under sunlight. The analog video image delay does not exceed 0.3 seconds, and the network camera delay does not exceed 0.4 seconds. The front-end feedback data is visible in real time.

Bidirectional transmission: The images and information collected by the front-end are transmitted to the back-end robot remote controller through the front-end transmitter. The back-end robot remote controller can send control instructions to the robot to realize bidirectional data transmission of the robot intelligent communication system;

Remote control: At the same site, one remote control can control multiple robots or multiple remote controls can control multiple robots to achieve collaborative operations of robot clusters.

Long transmission distance: 1.5 kilometers in urban environment, 2-5 kilometers in line of sight;

Simple operation: voice intercom is possible, multiple rockers, switches and buttons are set, making it easy to operate in an emergency;

Networking function: MESH self-organizing network, the number of relay hops is not less than 9 hops, and the networking nodes are not less than 64;

Long working time: built-in battery, with a battery life of up to 4 to 5 hours, which can work for a long time in emergency situations;

High protection level: IP67 protection design, convenient for use in harsh environments.

Product Parameters

Model	ZKMANET2152U M	Brand	ZKMANET
	System	Windows 10	
Parameter	Screen dimension	10.1inch FHD Screen	
	Definition	1280*800px	
	Light	1000 nits	
	Video output	1-8Channels V	'ideo Display
RF Parameter	Working Frequency	1.4GHz	
	Bandwidth	5/10/20/40MH	z,20MHz(Typical)
	RF Channels	2T2R	
	RF power	4W	
	RF Interface	TNC*2,SMA*1	
Interface parameter	Network Interface	RJ45	
	PTT Interface	Waterproof K h	nead MIC
	Charging interface	Waterproof DC Head	
	Network capacity	No less than 9 Hops,10nodes(Can be customized)	
Network parameter	Transmission range	1.5(NLOS) 2-5km(LOS)	
	Data rate	82Mbps	
	Encryption	AES	
	Public network	4G/5G	
hypical	Dimension	373*241.5*57mm	
Physical parameter/Environment	Weight	2.9kg(W/Batte	ry)
	Working temperature	-20ºC-60ºC	
	Protection rank	IP66	
	Working voltage	12V	
Electric character	Battery capacity	12Ah	
	Power consumption	Less than High	n Power

Panel Description						
Double Screen Ugv Eod Special Equipment RF Remote Controller for Harse Environment						
1: MESH antenna Interface						
2: 4G/5G Sim card interface						
3:4G antenna interface 4: MESH antenna interface						
Double Screen Ugv Eod Special Equipment RF Remote Controller for Harse Environment						
1. Power interface						
2. Network interface						
3. Power display 4. PTT interface						
Application						
SPECIAL EQUIPMENT UGV EOD REMOTE CONTROLLER						
Company						
Company						
Profile						
market-oriented, focusing on developing products suitable for emergency communication, non-combat mission communication systems for forces, special robot intelligent communication products, and auxiliary decision-making systems. The company is dedicated to providing customers with wireless broadband communication products and auxiliary decision-making system research and production under complex conditions. Double Screen Ugv Eod Special Equipment RF Remote Controller for Harse Environment Double Screen Ugv Eod Special Equipment RF Remote Controller for Harse Environment Double Screen Ugv Eod Special Equipment RF Remote Controller for Harse Environment						
Certifications						
Double Screen Ugv Eod Special Equipment RF Remote Controller for Harse Environment						
FAQ						
Double Screen Ugv Eod Special Equipment RF Remote Controller for Harse Environment						
Double Screen Ugv Eod Special Equipment RF Remote Controller for Harse Environment						

ZVMINET Zhongke Lianxun (Shenzhen) Technology Co., Ltd							
Q	+86 13266718951	Info@ct	hinamanet.com	zkmanet.com			
203-B161, Block	, , , ,	0,	79 Nanhai Avenue, Yans ct, Shenzhen, China	han Community, Merchants			