

# ZKMANET2441UM 100g Compact Portable Airborne Radio Data Link For Drone UAV

## **Basic Information**

Place of Origin: ShenzhenBrand Name: ZKMANETCertification: CE,FCC

Model Number: ZKMANET2441UM

Minimum Order Quantity:

Price: USD 99~999
Packaging Details: Carton

• Delivery Time: 10 working days

• Payment Terms: L/C, D/A, D/P, T/T, Western Union,

MoneyGram

• Supply Ability: 1000 pieces per year



## **Product Specification**

RF Channel: 1T2R
Output Power: 2W
Range: 30KM
Weight: 142g

• Size: 103.5\*61.5\*22mm

• Interface: RJ45,TTL

RF: 800GHz 1.4GHz 2.4GHz
Application: Drone UAV Aircraft
Highlight: UAV Airborne Radio data link,

Compact Airborne Radio data link, Drone Airborne Radio data link



# More Images





# **Product Description**

ZKMANET2441UM 100g Compact Portable Airborne Radio Data Link For Drone UAV

Product Description

The ZKManet2441UM is a compact and portable airborne radio with HD and stable image quality. It adopts the current leading OFDM modulation technology, allowing for capturing high-quality images in high-speed motion and real-time transmission in non-line-of-sight (NLOS) conditions. Encryption is applied to the images and data during transmission, supporting a transmission rate of 30Mbps and a range of 30KM for air-to-ground transmission. It is well-suited for long-term and high-data-flow wireless transmission applications, such as UAVs, USVs, and robots.

#### Features

- \* Range no less than 30 km(LOS)
- \* Supports 3 bands (800MHz/1.4GHz/2.4GHz)
- \* IP transparent data transmission
- \* Compact size and light weight
- \* Rugged aluminum alloy housing
- \* Low power consumption
- \* With TTL and RJ45 port

#### **Product Parameters**

Model	ZKMANET2441UM	Brand	ZKMANET	
RF Parameters	Frequency	800MHz/1.4GHz /2.4GHz		
	Bandwidth	1.4MHz/3MHz/5MHz/10MHz/20MHz		
	RF Channel	1T2R		
	Output Power	33dBm		
	Range	30km (LOS)		
Network Parameters	Network Mode	One-to-one and one-to-many		
	Data Rate	30Mbps(Max)		
	Encryption	ZUC/SNOW3G/AES Optional		
Physical/ Environment	Dimensions	103.5*61.5*22mm		
	Weight	142g		
	Working Temp	-40°C~+65°C		
Electronic Parameters	Power Supply	DC12V		
	Power Consumption	<12W		
Other	Data Interface	RJ45*2,TTL*3		

## Panel Description

- 1. Audio Interface
- 2. RA232 Interface\*3
- 3. RJ45 Interface-1
- 4. RJ45 Interface-2
- 5. Power Input Interface
- Link Status Indicator When the device works as an access node, if the connection with the central node is normal, the indicator will flash. When the device works as a central node, this indicator will be always on.
- 2. Signal Indicator
- 3. Power Indicator
- 4. RF Antenna-2
- 5. RF Antenna-1

## Application



## Company Profile

Zhongke Lianxun (Shenzhen) Co.,Ltd has multiple patents with independent intellectual property rights, has established a sound quality system and national standard system that comply with ISO9001 standards, and strictly produces products in accordance with national standards and internationally recognized standards such as CCC, CE, FCC, etc. It has obtained the Radio Transmission Equipment Model Approval Certificate issued by the Ministry of Industry and Information Technology of China and has passed the wireless product testing certification of the Ministry of Public Security.

2W 30km Compact and Portable Airborne Uav Dawn Swatiand Portable A

Certifications			
2W 30km Compact and Portable Airl	oorne Uav Drone Data Link Ra	adio	
Our Advantages			

# ZYMVNET Zhongke Lianxun (Shenzhen) Technology Co., Ltd



+86 13266718951



Info@chinamanet.com



zkmanet.com

203-B161, Block B, Garden City Digital Building, No.1079 Nanhai Avenue, Yanshan Community, Merchants Street, Nanshan District, Shenzhen, China