

## ZKMANET2441UM Ultra High Power Airborne Drone Data Link For UAV DRONE VTOL

Our Product Introduction

for more products please visit us on [zkmanet.com](http://zkmanet.com)

### Basic Information

- Place of Origin: Shenzhen
- Brand Name: ZKMANET
- Certification: CE,FCC
- Model Number: ZKMANET2441UM
- Minimum Order Quantity: 1
- Price: USD 99~999
- Packaging Details: Carton
- Delivery Time: 10 working days
- Payment Terms: L/C, D/A, D/P, T/T, Western Union, MoneyGram
- Supply Ability: 1000 pieces per year

**ZKMANET**



### Product Specification

- RF Channel: 1T2R
- Output Power: 2W
- Range: 30KM
- Weight: 142g
- Size: 103.5\*61.5\*22mm
- Interface: RJ45,TTL
- RF: 800GHz 1.4GHz 2.4GHz
- Application: Drone UAV Aircraft
- Highlight: Drone Data Link For UAV VTOL, Airborne Drone Data Link, Ultra High Power Drone Data Link

**ZKMANET**



### More Images

**ZKMANET**



**ZKMANET**



### Product Description

**ZKMANET2441UM Ultra High Power Airborne Drone Data Link For UAV DRONE VTOL**

Product Description

The ZKManet2441UM is a compact and portable airborne radio with HD and stable image quality. It adopts the current leading OFDM modulation technology, allowing for capturing high-quality images in high-speed motion and real-time transmission in non-line-of-sight (NLOS) conditions. Encryption is applied to the images and data during transmission, supporting a transmission rate of 30Mbps and a range of 30KM for air-to-ground transmission. It is well-suited for long-term and high-data-flow wireless transmission applications, such as UAVs, USVs, and robots.

#### Features

- \* Range no less than 30 km(LOS)
- \* Supports 3 bands (800MHz/1.4GHz/2.4GHz)
- \* IP transparent data transmission
- \* Compact size and light weight
- \* Rugged aluminum alloy housing
- \* Low power consumption
- \* With TTL and RJ45 port

#### Product Parameters

Model	ZKMANET2441UM	Brand	ZKMANET
RF Parameters	Frequency	800MHz/1.4GHz /2.4GHz	
	Bandwidth	1.4MHz/3MHz/5MHz/10MHz/20MHz	
	RF Channel	1T2R	
	Output Power	33dBm	
	Range	30km (LOS)	
Network Parameters	Network Mode	One-to-one and one-to-many	
	Data Rate	30Mbps(Max)	
	Encryption	ZUC/SNOW3G/AES Optional	
Physical/ Environment	Dimensions	103.5*61.5*22mm	
	Weight	142g	
	Working Temp	-40°C~+65°C	
Electronic Parameters	Power Supply	DC12V	
	Power Consumption	<12W	
Other	Data Interface	RJ45*2,TTL*3	

#### Panel Description

1. Audio Interface
2. RA232 Interface\*3
3. RJ45 Interface-1
4. RJ45 Interface-2
5. Power Input Interface

1. Link Status Indicator - When the device works as an access node, if the connection with the central node is normal, the indicator will flash. When the device works as a central node, this indicator will be always on.
2. Signal Indicator
3. Power Indicator
4. RF Antenna-2
5. RF Antenna-1

#### Application



#### Company Profile

Zhongke Lianxun (Shenzhen) Co.,Ltd has multiple patents with independent intellectual property rights, has established a sound quality system and national standard system that comply with ISO9001 standards, and strictly produces products in accordance with national standards and internationally recognized standards such as CCC, CE, FCC, etc. It has obtained the Radio Transmission Equipment Model Approval Certificate issued by the Ministry of Industry and Information Technology of China and has passed the wireless product testing certification of the Ministry of Public Security.

2W 30km Compact and Portable Airborne Uav Drone Data Link Radio 2W 30km Compact and Portable Airborne Uav Drone Data Link Radio 2W 30km Compact and Portable Airborne Uav Drone Data Link Radio

#### Certifications

2W 30km Compact and Portable Airborne Uav Drone Data Link Radio

#### Our Advantages

**ZKMANET Zhongke Lianxun (Shenzhen) Technology Co., Ltd**

+86 13266718951

Info@chinamanet.com

zkmanet.com

203-B161, Block B, Garden City Digital Building, No.1079 Nanhai Avenue, Yanshan Community, Merchants Street, Nanshan District, Shenzhen, China